

| | | | | | | |
|--|-------------------|------------------------------------|--|--|--|--|
| | | | | | | |
| | DATI TECNICI | | | | | |
| | SECONDO UNI 10348 | | | | | |
| | | | | | | |
| | 1) | UNIT | | | | |
| | 2) | 2 KRCT | | | | |
| | 3) | 2 RCT - 4 RCT | | | | |
| | 4) | CFE-AR 400 | | | | |
| | 5) | CFE-AR 800 | | | | |
| | 6) | GT 300 - GT 400 - GT 500 | | | | |
| | 7) | 3500 MICRONOX | | | | |
| | 8) | INSIEME | | | | |
| | 9) | 3500 | | | | |
| | 10) | 3700 | | | | |
| | 11) | 3900 | | | | |
| | 12) | 3000 KLMC | | | | |
| | 13) | ATR | | | | |
| | 14) | DOMUS | | | | |
| | 15) | ATK | | | | |
| | 16) | BENEFIT - ESTERNA | | | | |
| | 17) | RESIDENCE - BENESSERE - PRONTACQUA | | | | |

UNIT

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|---|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | | (1) | (2) |
| CON BRUCIATORE DI GASOLIO (fiamma blu) | | | | | | | | | | |
| UNIT 24 LOW NOx | 24.0 | 25.8 | 93.0 | 91.7 | 0,1 | 5.8 | 1.2 | 132 | 13.6 | |
| UNIT 31 LOW NOx | 31.0 | 33.2 | 93.4 | 91.6 | 0,1 | 6.0 | 0.6 | 138 | 13.6 | |
| UNIT 36 LOW NOx | 36.0 | 38.7 | 93.0 | 91.5 | 0,1 | 6.2 | 0.8 | 142 | 13.6 | |
| UNIT 49 LOW NOx | 49.0 | 52.7 | 93.0 | 91.5 | 0,1 | 6.5 | 0.5 | 151 | 13.8 | |
| UNIT 60 LOW NOx | 60.0 | 65.0 | 92.3 | 91.0 | 0,1 | 7.1 | 0.6 | 166 | 13.9 | |
| CON BRUCIATORE DI GASOLIO (fiamma gialla) | | | | | | | | | | |
| UNIT 4N | 26.1 | 28.5 | 91.6 | 90.3 | 0,1 | 7.4 | 1.0 | 163 | 13.0 | 300 |
| UNIT 5N | 32.2 | 34.8 | 92.5 | 91.0 | 0,1 | 6.6 | 0.8 | 140 | 12.4 | 300 |
| UNIT 6N | 40.8 | 44.0 | 92.7 | 91.5 | 0,1 | 6.4 | 0.8 | 145 | 13.4 | 180 |
| UNIT 7N | 48.2 | 52.7 | 91.5 | 90.2 | 0,1 | 7.6 | 1.0 | 168 | 13.1 | 180 |
| UNIT 8N | 60.0 | 65.7 | 91.3 | 90.4 | 0,1 | 8.1 | 0.6 | 176 | 12.9 | 190 |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| UNIT 4BF | 25.0 | 27.0 | 92.6 | 91.3 | 0,1 | 6.3 | 1.1 | 136 | 10.5 | 110 |
| UNIT 5BF | 32.0 | 34.5 | 92.8 | 91.5 | 0,1 | 6.4 | 0.8 | 139 | 10.5 | 120 |
| UNIT 6BF | 40.4 | 43.7 | 92.4 | 91.2 | 0,1 | 6.9 | 0.6 | 149 | 10.4 | 120 |
| UNIT 7BF | 46.5 | 50.9 | 91.4 | 90.0 | 0,1 | 8.1 | 0.5 | 162 | 9.5 | 120 |
| (1) con delta T = 50 °C | | | | | | | | | | |

KRCT

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| 2 KRCT 4 | 27.0 | 29.9 | 90.3 | 86.8 | 0.1 | 7.0 | 2.6 | 151 | 12.6 | |
| 2 KRCT 5/1 | 31.6 | 34.8 | 90.8 | 87.1 | 0.1 | 7.2 | 2 | 148 | 12.0 | |
| 2 KRCT 6 | 44.2 | 49.1 | 90.0 | 87.1 | 0.1 | 8.1 | 1.9 | 175 | 12.7 | |
| 2 KRCT 7 | 53.5 | 59.1 | 90.5 | 87.2 | 0.1 | 8.3 | 1.2 | 178 | 12.6 | |
| 2 KRCT 8 | 62.8 | 69.0 | 91.0 | 87.7 | 0.1 | 8.0 | 1 | 172 | 12.7 | |
| 2 KRCT 9 | 70.9 | 78.4 | 90.4 | 86.9 | 0.1 | 8.2 | 1.3 | 170 | 12.1 | |
| 2 KRCT 10 | 79.1 | 87.6 | 90.3 | 87.2 | 0.1 | 8.1 | 1.6 | 178 | 12.9 | |
| 2 KRCT 11 | 87.2 | 96.9 | 90.0 | 87.0 | 0.1 | 8.0 | 2 | 169 | 12.4 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| 2 KRCT 4 | 27.0 | 29.9 | 90.3 | 86.8 | 0.1 | 7.0 | 2.7 | 142 | 9.6 | |
| 2 KRCT 5/1 | 31.6 | 34.8 | 90.8 | 87.1 | 0.1 | 7.2 | 2 | 141 | 9.3 | |
| 2 KRCT 6 | 44.2 | 49.1 | 90.0 | 87.1 | 0.1 | 8.1 | 1.9 | 163 | 9.6 | |
| 2 KRCT 7 | 53.5 | 59.1 | 90.5 | 87.2 | 0.1 | 8.3 | 1.2 | 167 | 9.6 | |
| 2 KRCT 8 | 62.8 | 69.0 | 91.0 | 87.7 | 0.1 | 8.0 | 1 | 162 | 9.6 | |
| 2 KRCT 9 | 70.9 | 78.4 | 90.4 | 86.9 | 0.1 | 8.2 | 1.4 | 161 | 9.3 | |
| 2 KRCT 10 | 79.1 | 87.6 | 90.3 | 87.2 | 0.1 | 8.1 | 1.6 | 165 | 9.7 | |
| 2 KRCT 11 | 87.2 | 96.9 | 90.0 | 87.0 | 0.1 | 8.0 | 2 | 159 | 9.4 | |
| (1) con delta T = 50 °C | | | | | | | | | | |

RCT

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| 2 RCT 4 | 27.0 | 29.9 | 90.3 | 87.3 | 0.1 | 7.0 | 2.6 | 151 | 12.6 | |
| 2 RCT 5/1 | 31.6 | 34.8 | 90.8 | 87.6 | 0.1 | 7.2 | 2 | 148 | 12.0 | |
| 2 RCT 6 | 44.2 | 49.1 | 90.0 | 87.6 | 0.1 | 8.1 | 1.9 | 175 | 12.7 | |
| 2 RCT 7 | 53.5 | 59.1 | 90.5 | 87.7 | 0.1 | 8.3 | 1.2 | 178 | 12.6 | |
| 2 RCT 8 | 62.8 | 69.0 | 91.0 | 88.2 | 0.1 | 8.0 | 1 | 172 | 12.7 | |
| 2 RCT 9 | 70.9 | 78.4 | 90.4 | 87.4 | 0.1 | 8.2 | 1.3 | 170 | 12.1 | |
| 2 RCT 10 | 79.1 | 87.6 | 90.3 | 87.7 | 0.1 | 8.1 | 1.6 | 178 | 12.9 | |
| 2 RCT 11 | 87.2 | 96.9 | 90.0 | 87.5 | 0.1 | 8.0 | 2 | 169 | 12.4 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| 2 RCT 4 | 27.0 | 29.9 | 90.3 | 87.3 | 0.1 | 7.0 | 2.7 | 142 | 9.6 | |
| 2 RCT 5/1 | 31.6 | 34.8 | 90.8 | 87.6 | 0.1 | 7.2 | 2 | 141 | 9.3 | |
| 2 RCT 6 | 44.2 | 49.1 | 90.0 | 87.6 | 0.1 | 8.1 | 1.9 | 163 | 9.6 | |
| 2 RCT 7 | 53.5 | 59.1 | 90.5 | 87.7 | 0.1 | 8.3 | 1.2 | 167 | 9.6 | |
| 2 RCT 8 | 62.8 | 69.0 | 91.0 | 88.2 | 0.1 | 8.0 | 1 | 162 | 9.6 | |
| 2 RCT 9 | 70.9 | 78.4 | 90.4 | 87.4 | 0.1 | 8.2 | 1.4 | 161 | 9.3 | |
| 2 RCT 10 | 79.1 | 87.6 | 90.3 | 87.7 | 0.1 | 8.1 | 1.6 | 165 | 9.7 | |
| 2 RCT 11 | 87.2 | 96.9 | 90.0 | 87.5 | 0.1 | 8.0 | 2 | 159 | 9.4 | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| 4 RCT 5 | 86.0 | 95.3 | 90.2 | 87.0 | 0.1 | 8.5 | 1.3 | 188 | 13.1 | |
| 4 RCT 6 | 103.5 | 114.8 | 90.2 | 87.2 | 0.1 | 8.4 | 1.5 | 177 | 12.4 | |
| 4 RCT 7 | 120.9 | 133.7 | 90.4 | 87.6 | 0.1 | 7.9 | 1.7 | 180 | 13.6 | |
| 4 RCT 8 | 138.3 | 152.9 | 90.5 | 87.8 | 0.1 | 8.0 | 1.5 | 186 | 13.8 | |
| 4 RCT 9 | 156.9 | 173.8 | 90.3 | 87.8 | 0.1 | 8.3 | 1.4 | 177 | 12.5 | |
| 4 RCT 10 | 182.5 | 201.1 | 90.8 | 88.3 | 0.1 | 8.1 | 1.1 | 179 | 13.0 | |
| 4 RCT 11 | 202.3 | 223.3 | 90.6 | 88.3 | 0.1 | 8.4 | 1 | 184 | 13.0 | |
| 4 RCT 12 | 222.1 | 245.3 | 90.5 | 88.2 | 0.1 | 8.5 | 0.9 | 190 | 13.2 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| 4 RCT 5 | 86.0 | 95.3 | 90.2 | 87.0 | 0.1 | 8.5 | 1.3 | 172 | 9.7 | |
| 4 RCT 6 | 103.5 | 114.8 | 90.2 | 87.2 | 0.1 | 8.4 | 1.5 | 163 | 9.2 | |
| 4 RCT 7 | 120.9 | 133.7 | 90.4 | 87.6 | 0.1 | 7.9 | 1.6 | 164 | 9.9 | |
| 4 RCT 8 | 138.3 | 152.9 | 90.5 | 87.8 | 0.1 | 8.0 | 1.5 | 166 | 9.9 | |
| 4 RCT 9 | 156.9 | 173.8 | 90.3 | 87.8 | 0.1 | 8.3 | 1.4 | 163 | 9.3 | |
| 4 RCT 10 | 182.5 | 201.1 | 90.8 | 88.3 | 0.1 | 8.1 | 1.1 | 165 | 9.7 | |
| 4 RCT 11 | 202.3 | 223.3 | 90.6 | 88.3 | 0.1 | 8.4 | 1 | 171 | 9.7 | |
| 4 RCT 12 | 222.1 | 245.3 | 90.5 | 88.2 | 0.1 | 8.5 | 1 | 173 | 9.7 | |

| | | | | | | | | | | |
|---|--|--|--|--|--|--|--|--|--|--|
| (1) con $\Delta T = 50\text{ }^\circ\text{C}$ | | | | | | | | | | |
|---|--|--|--|--|--|--|--|--|--|--|

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|------------------------------|-------|-------------------------------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al fumi °C (delta T) | CO2 % | |
| | | | | | Bruc. Spento | Bruc. Funz. | | | |
| | kW | kW | % | % | % | % | % | | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | |
| CFE-AR 405 | 139 | 153.8 | 90.4 | 89.2 | 0.1 | 8.3 | 1.3 | 171 | 12.1 |
| CFE-AR 407 | 209.0 | 230.9 | 90.5 | 89.5 | 0,1 | 8.3 | 1.2 | 178 | 12.6 |
| CFE-AR 408 | 244.0 | 269.3 | 90.6 | 89.7 | 0,1 | 8.3 | 1.1 | 180 | 12.8 |
| CFE-AR 409 | 279.0 | 307.9 | 90.6 | 89.9 | 0,1 | 8.3 | 1.1 | 182 | 12.9 |
| CFE-AR 410 | 314.0 | 346.2 | 90.7 | 90.1 | 0,1 | 8.4 | 0.9 | 183 | 12.9 |
| CFE-AR 411 | 349.0 | 383.9 | 90.9 | 90.5 | 0,1 | 8.3 | 0.8 | 183 | 13.0 |
| CFE-AR 412 | 384.0 | 422.4 | 90.9 | 90.9 | 0,1 | 8.4 | 0.7 | 184 | 13.0 |
| CFE-AR 413 | 419.0 | 460.9 | 90.9 | 91.2 | 0,1 | 8.4 | 0.7 | 184 | 13.0 |
| CFE-AR 414 | 454.0 | 498.9 | 91.0 | 91.3 | 0,1 | 8.4 | 0.6 | 184 | 13.0 |
| CFE-AR 415 | 489.0 | 536.8 | 91.1 | 91.5 | 0,1 | 8.4 | 0.5 | 185 | 13.0 |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | |
| CFE-AR 405 | 139.0 | 153.8 | 90.4 | 89.2 | 0,1 | 8.3 | 1.3 | 162 | 9.2 |
| CFE-AR 406 | 174.0 | 192.5 | 90.4 | 89.4 | 0,1 | 8.3 | 1.3 | 164 | 9.3 |
| CFE-AR 407 | 209.0 | 230.9 | 90.5 | 89.5 | 0,1 | 8.3 | 1.2 | 165 | 9.4 |
| CFE-AR 408 | 244.0 | 269.3 | 90.6 | 89.7 | 0,1 | 8.3 | 1.1 | 166 | 9.5 |
| CFE-AR 409 | 279.0 | 307.9 | 90.6 | 89.9 | 0,1 | 8.3 | 1.1 | 167 | 9.5 |
| CFE-AR 410 | 314.0 | 346.2 | 90.7 | 90.1 | 0,1 | 8.4 | 0.9 | 168 | 9.5 |
| CFE-AR 411 | 349.0 | 383.9 | 90.9 | 90.5 | 0,1 | 8.3 | 0.8 | 168 | 9.6 |
| CFE-AR 412 | 384.0 | 422.4 | 90.9 | 90.9 | 0,1 | 8.4 | 0.7 | 169 | 9.6 |
| CFE-AR 413 | 419.0 | 460.9 | 90.9 | 91.2 | 0,1 | 8.4 | 0.7 | 169 | 9.6 |
| CFE-AR 414 | 454.0 | 498.9 | 91.0 | 91.3 | 0,1 | 8.4 | 0.6 | 169 | 9.6 |
| CFE-AR 415 | 489.0 | 536.8 | 91.1 | 91.5 | 0,1 | 8.4 | 0.5 | 170 | 9.6 |
| (1) con delta T = 50 °C | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | CO2 % | Potenza Elettrica Assorbita W |
|------------------------------|---------------------|----------|------------------|-----------------|---------------------|------------|---------------|-----------------|----------|--|
| | Utile | Focolare | Pn | a carico | Perdite al Bruc. | Camino | Perdite al | Temper. fumi | | |
| | kW | kW | % | rid. (30%) % | Spento % | Funz. % | Mantello % | °C (delta T) | | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| CFE-AR 807 | 406.0 | 451.1 | 90.0 | 89.3 | 0,1 | 9.2 | 0.8 | 204 | 13.1 | |
| CFE-AR 808 | 464.0 | 515 | 90.1 | 89.4 | 0,1 | 9.2 | 0.7 | 204 | 13.1 | |
| CFE-AR 809 | 522.0 | 579.4 | 90.1 | 89.5 | 0,1 | 9.2 | 0.7 | 204 | 13.1 | |
| CFE-AR 810 | 580.0 | 643.7 | 90.1 | 89.6 | 0,1 | 9.1 | 0.8 | 202 | 13.1 | |
| CFE-AR 811 | 638.0 | 707.3 | 90.2 | 89.7 | 0,1 | 9.1 | 0.7 | 201 | 13.1 | |
| CFE-AR 812 | 696.0 | 772.5 | 90.1 | 89.8 | 0,1 | 9 | 0.9 | 200 | 13.1 | |
| CFE-AR 813 | 754.0 | 835.9 | 90.2 | 89.8 | 0,1 | 8.9 | 0.9 | 199 | 13.2 | |
| CFE-AR 814 | 812.0 | 900.2 | 90.2 | 89.9 | 0,1 | 8.9 | 0.9 | 199 | 13.2 | |
| CFE-AR 815 | 870.0 | 964.5 | 90.2 | 90.0 | 0,1 | 8.9 | 0.9 | 200 | 13.3 | |
| CFE-AR 816 | 928.0 | 1027.7 | 90.3 | 90.0 | 0,1 | 8.9 | 0.8 | 200 | 13.3 | |
| CFE-AR 817 | 986.0 | 1093.1 | 90.2 | 90.0 | 0,1 | 8.8 | 1 | 199 | 13.4 | |
| CFE-AR 818 | 1,044.0 | 1156.1 | 90.3 | 90.1 | 0,1 | 8.8 | 0.9 | 199 | 13.4 | |
| CFE-AR 819 | 1,102.0 | 1220.4 | 90.3 | 90.5 | 0,1 | 8.7 | 1 | 198 | 13.5 | |
| CFE-AR 820 | 1,160.0 | 1284.6 | 90.3 | 90.7 | 0,1 | 8.7 | 1 | 198 | 13.5 | |
| CFE-AR 821 | 1,218.0 | 1347.3 | 90.4 | 90.8 | 0,1 | 8.7 | 0.9 | 198 | 13.5 | |
| CFE-AR 822 | 1,276.0 | 1413.1 | 90.3 | 91.2 | 0,1 | 8.7 | 1 | 198 | 13.5 | |
| CFE-AR 823 | 1,334.0 | 1475.7 | 90.4 | 91.3 | 0,1 | 8.6 | 1 | 196 | 13.5 | |
| CFE-AR 824 | 1,392.0 | 1539.8 | 90.4 | 91.6 | 0,1 | 8.5 | 1.1 | 194 | 13.5 | |
| CFE-AR 825 | 1,450.0 | 1602.2 | 90.5 | 91.9 | 0,1 | 8.5 | 1 | 194 | 13.5 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| CFE-AR 807 | 406.0 | 451.1 | 91.0 | 0,1 | 9.2 | 0.8 | 181 | 1,7 | | |
| CFE-AR 808 | 464.0 | 515 | 91.1 | 0,1 | 9.2 | 0.7 | 181 | 1,75 | | |
| CFE-AR 809 | 522.0 | 579.4 | 91.1 | 0,1 | 9.2 | 0.7 | 181 | 1,8 | | |
| CFE-AR 810 | 580.0 | 643.7 | 91.3 | 0,1 | 9.1 | 0.8 | 179 | 1,9 | | |
| CFE-AR 811 | 638.0 | 707.3 | 91.4 | 0,1 | 9.1 | 0.7 | 178 | 2,0 | | |
| CFE-AR 812 | 696.0 | 772.5 | 91.6 | 0,1 | 9 | 0.9 | 177 | 2,1 | | |
| CFE-AR 813 | 754.0 | 835.9 | 91.6 | 0,1 | 8.9 | 0.9 | 176 | 2,2 | | |
| CFE-AR 814 | 812.0 | 900.2 | 91.7 | 0,1 | 8.9 | 0.9 | 176 | 2,3 | | |
| CFE-AR 815 | 870.0 | 964.5 | 91.7 | 0,1 | 8.9 | 0.9 | 178 | 2,4 | | |
| CFE-AR 816 | 928.0 | 1027.7 | 91.7 | 0,1 | 8.9 | 0.8 | 178 | 2,5 | | |
| CFE-AR 817 | 986.0 | 1093.1 | 91.8 | 0,1 | 8.8 | 1 | 177 | 2,6 | | |
| CFE-AR 818 | 1,044.0 | 1156.1 | 91.8 | 0,1 | 8.8 | 0.9 | 177 | 2,7 | | |
| CFE-AR 819 | 1,102.0 | 1220.4 | 91.9 | 0,1 | 8.7 | 1 | 176 | 2,85 | | |
| CFE-AR 820 | 1,160.0 | 1284.6 | 91.9 | 0,1 | 8.7 | 1 | 176 | 3,0 | | |
| CFE-AR 821 | 1,218.0 | 1347.3 | 91.9 | 0,1 | 8.7 | 0.9 | 176 | 3,1 | | |
| CFE-AR 822 | 1,276.0 | 1413.1 | 92.0 | 0,1 | 8.7 | 1 | 176 | 3,2 | | |

| | | | | | | | | | | |
|-------------------------|---------|--------|------|-----|-----|-----|-----|-----|--|--|
| CFE-AR 823 | 1,334.0 | 1475.7 | 92.1 | 0,1 | 8.6 | 1 | 174 | 3,3 | | |
| CFE-AR 824 | 1,392.0 | 1539.8 | 92.1 | 0,1 | 8.5 | 1.1 | 172 | 3,4 | | |
| CFE-AR 825 | 1,450.0 | 1602.2 | 92.1 | 0,1 | 8.5 | 1 | 172 | 3,5 | | |
| (1) con delta T = 50 °C | | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| GT 304 | 90.0 | 99.8 | 90.2 | 91.8 | 0,1 | 9.1 | 0.7 | 190 | 13 | |
| GT 305 | 115.0 | 127.6 | 90.1 | 92.2 | 0,1 | 8.9 | 1 | 196 | 13 | |
| GT 306 | 150.0 | 166.7 | 90 | 92.1 | 0,1 | 8.8 | 1.2 | 194 | 13 | |
| GT 307 | 200.0 | 221 | 90.5 | 92.5 | 0,1 | 8.9 | 0.6 | 195 | 13 | |
| GT 308 | 260.0 | 287.3 | 90.5 | 92.1 | 0,1 | 8 | 1.5 | 175 | 13 | |
| GT 309 | 310.0 | 342.5 | 90.5 | 92.2 | 0,1 | 7.5 | 2 | 165 | 13 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| GT 304 | 90.0 | 99.8 | 90.2 | 91.8 | 0,1 | 9.1 | 0.7 | 185 | 9.7 | |
| GT 305 | 115.0 | 127.6 | 90.1 | 92.2 | 0,1 | 8.9 | 1 | 182 | 9.7 | |
| GT 306 | 150.0 | 166.7 | 90.0 | 92.1 | 0,1 | 8.8 | 1.2 | 179 | 9.7 | |
| GT 307 | 200.0 | 221 | 90.5 | 92.5 | 0,1 | 8.9 | 0.6 | 180 | 9.7 | |
| GT 308 | 260.0 | 287.3 | 90.5 | 92.1 | 0,1 | 8 | 1.5 | 162 | 9.7 | |
| GT 309 | 310.0 | 342.5 | 90.5 | 92.2 | 0,1 | 7.7 | 1.8 | 157 | 9.7 | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| GT 408 | 390.0 | 432 | 90.3 | 92.2 | 0,1 | 9.1 | 0.7 | 200 | 13 | |
| GT 409 | 450.0 | 498 | 90.4 | 92.1 | 0,1 | 9.1 | 0.6 | 200 | 13 | |
| GT 410 | 540.0 | 596 | 90.6 | 92.2 | 0,1 | 9 | 0.5 | 198 | 13 | |
| GT 411 | 600.0 | 661 | 90.8 | 92.3 | 0,1 | 8.8 | 0.4 | 200 | 13.5 | |
| GT 412 | 670.0 | 738 | 90.8 | 92.3 | 0,1 | 8.8 | 0.4 | 200 | 13.5 | |
| GT 413 | 720.0 | 787 | 91.5 | 92.7 | 0,1 | 8.1 | 0.4 | 185 | 13.5 | |
| GT 414 | 780.0 | 851 | 91.7 | 92.9 | 0,1 | 8.1 | 0.2 | 184 | 13.5 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| GT 408 | 390.0 | 432 | 90.2 | 92.2 | 0,1 | 9.1 | 0.7 | 185 | 9.7 | |
| GT 409 | 450.0 | 498 | 90.3 | 92.1 | 0,1 | 9.1 | 0.6 | 185 | 9.7 | |
| GT 410 | 540.0 | 596 | 90.5 | 92.2 | 0,1 | 9 | 0.5 | 184 | 9.7 | |
| GT 411 | 600.0 | 661 | 90.8 | 92.3 | 0,1 | 8.8 | 0.4 | 180 | 9.8 | |
| GT 412 | 670.0 | 738 | 90.8 | 92.3 | 0,1 | 8.8 | 0.4 | 181 | 9.8 | |
| GT 413 | 720.0 | 787 | 91.5 | 92.7 | 0,1 | 8.1 | 0.4 | 167 | 9.8 | |
| GT 414 | 780.0 | 851 | 91.7 | 92.9 | 0,1 | 8.1 | 0.2 | 167 | 9.8 | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| GT 514 | 812.0 | 899 | 90.3 | 90.9 | 0,1 | 8.7 | 1 | 192 | 13 | |
| GT 515 | 870.0 | 962 | 90.4 | 91 | 0,1 | 8.7 | 0.9 | 192 | 13 | |
| GT 516 | 928.0 | 1025 | 90.5 | 91.3 | 0,1 | 8.7 | 0.8 | 192 | 13 | |
| GT 517 | 986.0 | 1088 | 90.6 | 91.4 | 0,1 | 8.8 | 0.6 | 193 | 13 | |

| | | | | | | | | | | |
|------------------------------|---------|------|------|------|-----|-----|-----|-----|-----|--|
| GT 518 | 1,044.0 | 1152 | 90.6 | 91.4 | 0,1 | 8.7 | 0.6 | 191 | 13 | |
| GT 519 | 1,102.0 | 1215 | 90.7 | 91.6 | 0,1 | 8.6 | 0.7 | 190 | 13 | |
| GT 520 | 1,160.0 | 1279 | 90.7 | 91.6 | 0,1 | 8.6 | 0.7 | 190 | 13 | |
| GT 521 | 1,218.0 | 1341 | 90.8 | 91.8 | 0,1 | 8.5 | 0.7 | 186 | 13 | |
| GT 522 | 1,276.0 | 1405 | 90.8 | 91.8 | 0,1 | 8.5 | 0.7 | 186 | 13 | |
| GT 523 | 1,334.0 | 1471 | 90.7 | 91.9 | 0,1 | 8.5 | 0.8 | 186 | 13 | |
| GT 524 | 1,392.0 | 1533 | 90.8 | 91.9 | 0,1 | 8.3 | 0.9 | 183 | 13 | |
| GT 525 | 1,450.0 | 1597 | 90.8 | 92.1 | 0,1 | 8.3 | 0.9 | 183 | 13 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| GT 514 | 812.0 | 899 | 90.3 | 90.9 | 0,1 | 8.7 | 1 | 178 | 9.8 | |
| GT 515 | 870.0 | 962 | 90.4 | 91 | 0,1 | 8.7 | 0.9 | 178 | 9.8 | |
| GT 516 | 928.0 | 1025 | 90.5 | 91.3 | 0,1 | 8.7 | 0.8 | 178 | 9.8 | |
| GT 517 | 986.0 | 1088 | 90.6 | 91.4 | 0,1 | 8.8 | 0.6 | 180 | 9.8 | |
| GT 518 | 1,044.0 | 1152 | 90.6 | 91.4 | 0,1 | 8.7 | 0.7 | 179 | 9.8 | |
| GT 519 | 1,102.0 | 1215 | 90.7 | 91.6 | 0,1 | 8.6 | 0.7 | 177 | 9.8 | |
| GT 520 | 1,160.0 | 1279 | 90.7 | 91.6 | 0,1 | 8.6 | 0.7 | 177 | 9.8 | |
| GT 521 | 1,218.0 | 1341 | 90.8 | 91.8 | 0,1 | 8.5 | 0.7 | 175 | 9.8 | |
| GT 522 | 1,276.0 | 1405 | 90.8 | 91.8 | 0,1 | 8.5 | 0.7 | 175 | 9.8 | |
| GT 523 | 1,334.0 | 1471 | 90.7 | 91.9 | 0,1 | 8.5 | 0.8 | 175 | 9.8 | |
| GT 524 | 1,392.0 | 1533 | 90.8 | 91.9 | 0,1 | 8.3 | 0.9 | 171 | 9.8 | |
| GT 525 | 1,450.0 | 1597 | 90.8 | 92.1 | 0,1 | 8.3 | 0.9 | 171 | 9.8 | |
| (1) con delta T = 50 °C | | | | | | | | | | |

MICRONOX

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | CO2 % | Potenza |
|------------------------------|---------------------|----------|------------------|----------|-----------------------------------|-------------|------------------------|---------------------------------|-------|-----------------------------|
| | Utile | Focolare | Pn | a carico | Perdite al Camino Bruc. Spento | Bruc. Funz. | Perdite al Mantello | Temper. fumi °C (delta T) | | Elettrica Assorbita W |
| | kW | kW | % | % | % | % | % | (1) | | -2 |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| MICRONOX 3500 mN 90 | 106 | 115 | 92.2 | 91.8 | 0,1 | 7.2 | 0.6 | 151 | 10 | 400 |
| MICRONOX 3500 mN 205 | 237 | 256 | 92.6 | 92.5 | 0,1 | 7.2 | 0.2 | 151 | 10 | 400 |
| MICRONOX 3500 mN 280 | 323 | 349 | 92.6 | 92.6 | 0,1 | 7.3 | 0.2 | 152 | 10 | 850 |
| MICRONOX 3500 mN 350 | 409 | 442 | 92.5 | 92.6 | 0,1 | 7.3 | 0.2 | 152 | 10 | 1.550 |
| (1) con delta T = 50 °C | | | | | | | | | | |

INSIEME

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| INSIEME 23 G/R | 26.7 | 29.5 | 90.5 | 88.8 | 0,1 | 7.5 | 2.0 | 156 | 12.2 | 250 |
| INSIEME 23 G | 26.7 | 29.5 | 90.5 | 88.8 | 0,1 | 7.5 | 2.0 | 156 | 12.2 | 250 |
| INSIEME 29 G | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 157 | 13.5 | 250 |
| INSIEME 29 G/2 | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 157 | 13.5 | 350 |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| INSIEME 23 S | 26.7 | 29.5 | 90.5 | 88.8 | 0,1 | 7.5 | 2.0 | 150 | 9.5 | 250 |
| INSIEME 29 S | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 138 | 9.5 | 250 |
| INSIEME 29 S/2 | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 138 | 9.5 | 350 |
| INSIEME 29 BF | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 138 | 9.5 | 250 |
| INSIEME 29 BF/2 | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 138 | 9.5 | 350 |
| CON BRUCIATORE DI GAS GPL | | | | | | | | | | |
| INSIEME 23 S | 26.7 | 29.5 | 90.5 | 88.8 | 0,1 | 7.5 | 2.0 | 170 | 11.7 | 250 |
| INSIEME 29 S | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 158 | 11.7 | 250 |
| INSIEME 29 S/2 | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 158 | 11.7 | 350 |
| INSIEME 29 BF | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 158 | 11.7 | 250 |
| INSIEME 29 BF/2 | 31.6 | 34.7 | 91.1 | 88.0 | 0,1 | 6.9 | 2.0 | 158 | 11.7 | 350 |
| (1) con delta T = 50 °C | | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| RIELLO 3500.S 75 | 87.2 | 96.2 | 90.6 | 87.7 | 0,1 | 7.4 | 1.9 | 163 | 13.0 | |
| RIELLO 3500.S 90 | 104.6 | 116.1 | 90.1 | 87.6 | 0,1 | 8.3 | 1.6 | 174 | 12.3 | |
| RIELLO 3500.S 110 | 127.9 | 141.8 | 90.2 | 87.2 | 0,1 | 6.9 | 2.9 | 155 | 13.3 | |
| RIELLO 3500.S 135 | 154.0 | 170.3 | 90.4 | 87.5 | 0,1 | 7.6 | 2.0 | 165 | 12.9 | |
| RIELLO 3500.S 160 | 186.7 | 206.7 | 90.3 | 87.2 | 0,1 | 7.6 | 2.0 | 166 | 12.8 | |
| RIELLO 3500.S 190 | 219.6 | 243.0 | 90.4 | 87.6 | 0,1 | 7.8 | 1.8 | 168 | 12.7 | |
| RIELLO 3500.S 245 | 286.0 | 315.7 | 90.6 | 88.5 | 0,1 | 8.0 | 1.4 | 171 | 12.5 | |
| RIELLO 3500.S 290 | 335.5 | 370.3 | 90.6 | 88.5 | 0,1 | 8.0 | 1.4 | 168 | 12.4 | |
| RIELLO 3500.S 350 | 407.0 | 447.7 | 90.9 | 88.9 | 0,1 | 7.8 | 1.2 | 167 | 12.5 | |
| RIELLO 3500.S 390 | 453.5 | 500.0 | 90.7 | 88.9 | 0,1 | 8.1 | 1.2 | 172 | 12.4 | |
| RIELLO 3500.S 455 | 528.0 | 581.4 | 90.8 | 88.4 | 0,1 | 7.6 | 1.6 | 165 | 12.9 | |
| RIELLO 3500.S 490 | 569.7 | 627.9 | 90.7 | 88.5 | 0,1 | 7.8 | 1.4 | 168 | 12.6 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| RIELLO 3500.S 75 | 87.2 | 96.2 | 90.6 | 87.7 | 0,1 | 7.4 | 2.0 | 150 | 9.7 | |
| RIELLO 3500.S 90 | 104.6 | 116.1 | 90.1 | 87.6 | 0,1 | 8.3 | 1.6 | 161 | 9.2 | |
| RIELLO 3500.S 110 | 127.9 | 141.8 | 90.2 | 87.2 | 0,1 | 6.9 | 2.9 | 143 | 9.9 | |
| RIELLO 3500.S 135 | 154.0 | 170.3 | 90.4 | 87.5 | 0,1 | 7.6 | 1.9 | 154 | 9.6 | |
| RIELLO 3500.S 160 | 186.7 | 206.7 | 90.3 | 87.2 | 0,1 | 7.6 | 2.1 | 155 | 9.7 | |
| RIELLO 3500.S 190 | 219.6 | 243.0 | 90.4 | 87.6 | 0,1 | 7.9 | 1.8 | 157 | 9.5 | |
| RIELLO 3500.S 245 | 286.0 | 315.7 | 90.6 | 88.5 | 0,1 | 8.0 | 1.4 | 159 | 9.4 | |
| RIELLO 3500.S 290 | 335.5 | 370.3 | 90.6 | 88.5 | 0,1 | 8.0 | 1.4 | 157 | 9.3 | |
| RIELLO 3500.S 350 | 407.0 | 447.7 | 90.9 | 88.9 | 0,1 | 7.8 | 1.3 | 155 | 9.4 | |
| RIELLO 3500.S 390 | 453.5 | 500.0 | 90.7 | 88.9 | 0,1 | 8.1 | 1.2 | 160 | 9.3 | |
| RIELLO 3500.S 455 | 528.0 | 581.4 | 90.8 | 88.4 | 0,1 | 7.6 | 1.6 | 153 | 9.6 | |
| RIELLO 3500.S 490 | 569.7 | 627.9 | 90.7 | 88.5 | 0,1 | 7.8 | 1.5 | 156 | 9.5 | |
| (1) con delta T = 50°C | | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| RIELLO 3700.19 | 22.2 | 24.5 | 90.6 | 87.5 | 0,1 | 7.3 | 2.1 | 161 | 13.0 | |
| RIELLO 3700.27 | 31.2 | 34.5 | 90.4 | 86.9 | 0,1 | 7.2 | 2.3 | 158 | 12.9 | |
| RIELLO 3700.32 | 37.1 | 41.0 | 90.5 | 87.2 | 0,1 | 7.3 | 2.2 | 159 | 12.9 | |
| RIELLO 3700.43 | 49.7 | 55.0 | 90.4 | 87.3 | 0,1 | 7.6 | 2.1 | 163 | 12.7 | |
| RIELLO 3700.55 | 63.2 | 70.0 | 90.3 | 87.5 | 0,1 | 7.9 | 1.9 | 166 | 12.4 | |
| RIELLO 3700.67 | 77.3 | 85.5 | 90.4 | 87.7 | 0,1 | 7.8 | 1.8 | 165 | 12.5 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| RIELLO 3700.19 | 22.2 | 24.5 | 90.6 | 87.5 | 0,1 | 7.3 | 2.1 | 148 | 9.7 | |
| RIELLO 3700.27 | 31.2 | 34.5 | 90.4 | 86.9 | 0,1 | 7.2 | 2.4 | 145 | 9.6 | |
| RIELLO 3700.32 | 37.1 | 41.0 | 90.5 | 87.2 | 0,1 | 7.3 | 2.2 | 147 | 9.6 | |
| RIELLO 3700.43 | 49.7 | 55.0 | 90.4 | 87.3 | 0,1 | 7.6 | 2.0 | 152 | 9.5 | |
| RIELLO 3700.55 | 63.2 | 70.0 | 90.3 | 87.5 | 0,1 | 7.9 | 1.8 | 155 | 9.3 | |
| RIELLO 3700.67 | 77.3 | 85.5 | 90.4 | 87.7 | 0,1 | 7.8 | 1.8 | 154 | 9.4 | |
| (1) con delta T = 50°C | | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | CO2 % | Potenza Elettrica Assorbita W |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------|-------------------------------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | | | | | % | % | | | | |
| | kW | kW | % | % | % | % | (1) | (2) | | |
| CON BRUCIATORE DI GASOLIO | | | | | | | | | | |
| RIELLO 3900.80 | 93.0 | 103.2 | 90.1 | 88.3 | 0.1 | 6.6 | 3.3 | 154 | 14.0 | |
| RIELLO 3900.100 | 116.3 | 129.2 | 90.0 | 88.5 | 0.1 | 7.0 | 2.9 | 160 | 13.5 | |
| RIELLO 3900.130 | 151.2 | 167.6 | 90.2 | 88.8 | 0.1 | 7.1 | 2.7 | 167 | 14.0 | |
| RIELLO 3900.165 | 191.9 | 213.0 | 90.1 | 88.5 | 0.1 | 7.5 | 2.4 | 166 | 13.0 | |
| RIELLO 3900.200 | 232.6 | 258.4 | 90.0 | 88.2 | 0.1 | 7.6 | 2.3 | 168 | 13.0 | |
| RIELLO 3900.250 | 290.0 | 321.8 | 90.1 | 88.0 | 0.1 | 7.9 | 2.0 | 174 | 13.0 | |
| RIELLO 3900.300 | 345.0 | 382.9 | 90.1 | 88.0 | 0.1 | 7.9 | 2.0 | 180 | 13.5 | |
| RIELLO 3900.350 | 405.0 | 449.0 | 90.2 | 88.3 | 0.1 | 7.9 | 1.9 | 180 | 13.5 | |
| RIELLO 3900.400 | 465.0 | 515.0 | 90.3 | 88.6 | 0.1 | 7.8 | 1.9 | 183 | 14.0 | |
| RIELLO 3900.450 | 520.0 | 576.0 | 90.3 | 88.3 | 0.1 | 7.9 | 1.8 | 179 | 13.5 | |
| RIELLO 3900.500 | 580.0 | 641.0 | 90.5 | 88.8 | 0.1 | 7.7 | 1.8 | 180 | 14.0 | |
| RIELLO 3900.600 | 695.0 | 768.0 | 90.5 | 89.0 | 0.1 | 7.8 | 1.7 | 182 | 14.0 | |
| RIELLO 3900.700 | 810.0 | 896.0 | 90.4 | 89.0 | 0.1 | 7.8 | 1.8 | 178 | 13.5 | |
| RIELLO 3900.800 | 930.0 | 1,029.0 | 90.4 | 89.0 | 0.1 | 7.9 | 1.7 | 180 | 13.5 | |
| RIELLO 3900.900 | 1,045.0 | 1,156.0 | 90.4 | 89.2 | 0.1 | 8.0 | 1.6 | 175 | 13.0 | |
| RIELLO 3900.1000 | 1,165.0 | 1,284.0 | 90.7 | 89.5 | 0.1 | 7.7 | 1.5 | 181 | 14.0 | |
| RIELLO 3900.1250 | 1,450.0 | 1,602.0 | 90.5 | 88.8 | 0.1 | 8.1 | 1.3 | 185 | 13.5 | |
| RIELLO 3900.1500 | 1,745.0 | 1,926.0 | 90.6 | 89.1 | 0.1 | 8.2 | 1.2 | 180 | 13.0 | |
| RIELLO 3900.1750 | 2,035.0 | 2,244.0 | 90.7 | 89.2 | 0.1 | 8.1 | 1.2 | 184 | 13.5 | |
| RIELLO 3900.2000 | 2,325.0 | 2,560.0 | 90.8 | 89.2 | 0.1 | 8.1 | 1.1 | 178 | 13.0 | |
| RIELLO 3900.2500 | 2,905.0 | 3,192.0 | 91.0 | 89.4 | 0.1 | 8.0 | 1.0 | 182 | 13.5 | |
| RIELLO 3900.3000 | 3,490.0 | 3,839.0 | 90.9 | 89.2 | 0.1 | 8.2 | 0.9 | 180 | 13.0 | |
| CON BRUCIATORE DI GAS METANO | | | | | | | | | | |
| RIELLO 3900.80 | 93.0 | 103.2 | 90.1 | 88.3 | 0.1 | 6.6 | 3.3 | 136 | 9.8 | |
| RIELLO 3900.100 | 116.3 | 129.2 | 90.0 | 88.5 | 0.1 | 7.0 | 2.9 | 142 | 9.6 | |
| RIELLO 3900.130 | 151.2 | 167.6 | 90.2 | 88.8 | 0.1 | 7.1 | 2.7 | 146 | 9.8 | |
| RIELLO 3900.165 | 191.9 | 213.0 | 90.1 | 88.5 | 0.1 | 7.5 | 2.4 | 148 | 9.3 | |
| RIELLO 3900.200 | 232.6 | 258.4 | 90.0 | 88.2 | 0.1 | 7.6 | 2.4 | 149 | 9.3 | |
| RIELLO 3900.250 | 290.0 | 321.8 | 90.1 | 88.0 | 0.1 | 7.9 | 2.0 | 155 | 9.3 | |
| RIELLO 3900.300 | 345.0 | 382.9 | 90.1 | 88.0 | 0.1 | 7.9 | 2.0 | 159 | 9.6 | |
| RIELLO 3900.350 | 405.0 | 449.0 | 90.2 | 88.3 | 0.1 | 7.9 | 1.9 | 160 | 9.6 | |
| RIELLO 3900.400 | 465.0 | 515.0 | 90.3 | 88.6 | 0.1 | 7.8 | 1.9 | 160 | 9.8 | |
| RIELLO 3900.450 | 520.0 | 576.0 | 90.3 | 88.3 | 0.1 | 7.9 | 1.8 | 159 | 9.6 | |
| RIELLO 3900.500 | 580.0 | 641.0 | 90.5 | 88.8 | 0.1 | 7.7 | 1.8 | 158 | 9.8 | |
| RIELLO 3900.600 | 695.0 | 768.0 | 90.5 | 89.0 | 0.1 | 7.8 | 1.7 | 160 | 9.8 | |

| | | | | | | | | | | |
|-------------------------|---------|---------|------|------|-----|-----|-----|-----|-----|--|
| RIELLO 3900.700 | 810.0 | 896.0 | 90.4 | 89.0 | 0.1 | 7.8 | 1.8 | 157 | 9.6 | |
| RIELLO 3900.800 | 930.0 | 1,029.0 | 90.4 | 89.0 | 0.1 | 7.9 | 1.7 | 159 | 9.6 | |
| RIELLO 3900.900 | 1,045.0 | 1,156.0 | 90.4 | 89.2 | 0.1 | 8.0 | 1.6 | 157 | 9.3 | |
| RIELLO 3900.1000 | 1,165.0 | 1,284.0 | 90.7 | 89.5 | 0.1 | 7.7 | 1.6 | 158 | 9.8 | |
| RIELLO 3900.1250 | 1,450.0 | 1,602.0 | 90.5 | 88.8 | 0.1 | 8.1 | 1.4 | 163 | 9.6 | |
| RIELLO 3900.1500 | 1,745.0 | 1,926.0 | 90.6 | 89.1 | 0.1 | 8.2 | 1.2 | 161 | 9.3 | |
| RIELLO 3900.1750 | 2,035.0 | 2,244.0 | 90.7 | 89.2 | 0.1 | 8.1 | 1.2 | 163 | 9.6 | |
| RIELLO 3900.2000 | 2,325.0 | 2,560.0 | 90.8 | 89.2 | 0.1 | 8.1 | 1.0 | 160 | 9.3 | |
| RIELLO 3900.2500 | 2,905.0 | 3,192.0 | 91.0 | 89.4 | 0.1 | 8.0 | 1.0 | 162 | 9.6 | |
| RIELLO 3900.3000 | 3,490.0 | 3,839.0 | 90.9 | 89.2 | 0.1 | 8.2 | 0.9 | 161 | 9.3 | |
| | | | | | | | | | | |
| (1) con delta T = 50 °C | | | | | | | | | | |

KLMC

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | | |
| KLMC 4-C | 17.4 | 19.3 | 90.2 | 86.6 | 0.6 | 8.3 | 1.5 | 100 | 5.2 | |
| KLMC 4-CI | 17.4 | 19.3 | 90.2 | 86.6 | 0.6 | 8.3 | 1.5 | 100 | 5.2 | |
| KLMC 5-C | 23.2 | 25.7 | 90.3 | 86.8 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| KLMC 5-V | 23.2 | 25.7 | 90.3 | 86.8 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| KLMC 5-CI | 23.2 | 25.7 | 90.3 | 86.8 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| KLMC 5-IV | 23.2 | 25.7 | 90.3 | 86.8 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| KLMC 5-CIS | 23.2 | 25.7 | 90.3 | 86.9 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| KLMC 6-C | 29.0 | 32.2 | 90.1 | 86.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| KLMC 6-V | 29.0 | 32.2 | 90.1 | 86.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| KLMC 6-CI | 29.0 | 32.2 | 90.1 | 86.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| KLMC 6-IV | 29.0 | 32.2 | 90.1 | 86.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| KLMC 6-CIS | 29.0 | 32.2 | 90.1 | 86.6 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| (1) con delta T = 50 °C | | | | | | | | | | |

ATR

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | (1) | (2) | |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | | |
| ATR/A 14 | 15.7 | 17.4 | 90.2 | 87.6 | 0.6 | 8.3 | 1.5 | 100 | 5.2 | |
| ATR/A 14 IC | 15.7 | 17.4 | 90.2 | 87.6 | 0.6 | 8.3 | 1.5 | 100 | 5.2 | |
| ATR/A 20 | 23.2 | 25.7 | 90.3 | 87.6 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATR/A 20 I | 23.2 | 25.7 | 90.3 | 87.6 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATR/A 20 C | 23.2 | 25.7 | 90.3 | 87.6 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATR/A 20 IC | 23.2 | 25.7 | 90.3 | 87.6 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATR 20 ISC | 23.2 | 25.7 | 90.3 | 87.7 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATR/A 25 | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATR/A 25 I | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATR/A 25 C | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATR/A 25 IC | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATR 25 ISC | 29.0 | 32.2 | 90.1 | 87.6 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATR 27 | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATR 27 I | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATR 27 C | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATR 27 IC | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATR 37 | 43.60 | 48.3 | 90.3 | 90.1 | 0.6 | 7.2 | 2.5 | 86 | 5.0 | |
| ATR 37 I | 43.60 | 48.3 | 90.3 | 90.1 | 0.6 | 7.2 | 2.5 | 86 | 5.0 | |
| ATR 45 | 55.00 | 61 | 90.2 | 90.1 | 0.6 | 8.1 | 1.7 | 93 | 4.9 | |
| ATR 45 I | 55.00 | 61 | 90.2 | 90.1 | 0.6 | 8.1 | 1.7 | 93 | 4.9 | |
| ATR 56 | 63.50 | 70.5 | 90.1 | 90.0 | 0.6 | 7.8 | 2.2 | 103 | 5.8 | |
| ATR 56 I | 63.50 | 70.5 | 90.1 | 90.0 | 0.6 | 7.8 | 2.2 | 103 | 5.8 | |
| ATR 65 | 71.10 | 79.00 | 90.0 | 90 | 0.6 | 8.4 | 1.6 | 110 | 5.7 | |
| ATR 65 I | 71.10 | 79.00 | 90.0 | 90 | 0.6 | 8.4 | 1.6 | 110 | 5.7 | |
| (1) con delta T = 50 °C | | | | | | | | | | |

DOMUS

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | |
|------------------------------|---------------------|----------|------------------|-----------------------|-----------------------------------|-------------|------------------------|------------------------------------|----------|
| | Utile | Focolare | Pn | a carico rid.(30%) | Perdite al Camino Bruc. Spento | Bruc. Funz. | Perdite al Mantello | Temper. fumi °C (delta T) | CO2 % |
| | kW | kW | % | % | % | % | % | (1) | |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| DOMUS 26 | 25.8 | 28.5 | 90.50 | 89.3 | 0,6 | 6.8 | 2.7 | 81.5 | 5 |
| DOMUS 26 ISC | 25.8 | 28.5 | 90.50 | 92.5 | 0,6 | 6.9 | 2.6 | 115.5 | 7.3 |
| DOMUS 31 | 31.7 | 34.8 | 91.10 | 89.9 | 0,6 | 7.2 | 1.7 | 80 | 4.6 |
| DOMUS 31 IS | 31.7 | 34.86 | 90.90 | 93.0 | 0,6 | 5.9 | 3.2 | 111.5 | 8.4 |
| DOMUS 31 ISC | 31.7 | 34.86 | 90.90 | 93.0 | 0,6 | 5.9 | 3.2 | 111.5 | 8.4 |
| DOMUS KL 21 | 20.3 | 22.5 | 90.20 | 86.8 | 0,6 | 7.7 | 2.1 | 80 | 4.25 |
| DOMUS KL 26 | 25.8 | 28.4 | 90.80 | 88.3 | 0,6 | 7.4 | 1.8 | 83 | 4.63 |
| DOMUS KL 26 ISC | 25.8 | 28.5 | 90.50 | 92.5 | 0,6 | 6.9 | 2.6 | 115.5 | 7.3 |
| DOMUS KL 31 ISC | 31.7 | 34.86 | 90.90 | 93.0 | 0,6 | 5.9 | 3.2 | 111.5 | 8.4 |
| DOMUS KV 26 | 25.8 | 28.5 | 90.50 | 89.3 | 0,6 | 6.8 | 2.7 | 81.5 | 5 |
| DOMUS KV 26 ISC | 25.8 | 28.5 | 90.50 | 92.5 | 0,6 | 6.9 | 2.6 | 115.5 | 7.3 |
| DOMUS KV 31 | 31.7 | 34.8 | 91.10 | 89.9 | 0,6 | 7.2 | 1.7 | 80 | 4.6 |
| DOMUS KV 31 IS | 31.7 | 34.8 | 91.10 | 93 | 0,6 | 5.9 | 3 | 111.5 | 8.4 |
| DOMUS KV 31 ISC | 31.7 | 34.8 | 91.10 | 93 | 0,6 | 5.9 | 3 | 111.5 | 8.4 |
| DOMUS KV 39 | 38.8 | 42.7 | 90.90 | 89.7 | 0,6 | 6.9 | 2.2 | 86.5 | 5.3 |
| (1) con delta T = 50 °C | | | | | | | | | |

ATK

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | Potenza Elettrica Assorbita W | |
|------------------------------|---------------------|----------|------------------|---------------------|-------------------|-------------|---------------------|---------------------------|-------------------------------|-------|
| | Utile | Focolare | Pn | a carico rid. (30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | | |
| | kW | kW | % | % | % | % | % | | (1) | (2) |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | | |
| ATK 20 VI | 23.2 | 25.7 | 90.3 | 87.4 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATK 20 VIC | 23.2 | 25.7 | 90.3 | 87.4 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATK 20 VISC | 23.2 | 25.7 | 90.3 | 87.6 | 0.6 | 8.2 | 1.5 | 102 | 5.4 | |
| ATK 25 V | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATK 25 VC | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATK 25 VI | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATK 25 VIC | 29.0 | 32.2 | 90.1 | 87.5 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATK 25 VISC | 29.0 | 32.2 | 90.1 | 87.7 | 0.6 | 8.4 | 1.5 | 103 | 5.3 | |
| ATK/60 27 V | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATK/60 27 VC | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATK/60 27 VI | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATK/60 27 VIC | 31.4 | 34.8 | 90.2 | 90.1 | 0.6 | 7.3 | 2.5 | 86 | 5.1 | |
| ATK 37 VI | 43.6 | 48.3 | 90.3 | 90.1 | 0.6 | 7.2 | 2.5 | 86 | 5.0 | |
| ATK 37 VIC | 43.6 | 48.3 | 90.3 | 90.1 | 0.6 | 7.2 | 2.5 | 86 | 5.0 | |
| (1) con delta T = 50 °C | | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | Temper. °C (delta T) | CO2 % |
|------------------------------|---------------------|----------|------------------|-----------------------|--------------------------------------|----------------|---------------------------|----------------------------|----------|
| | Utile | Focolare | Pn | a carico rid.(30%) | Perdite al Camino Bruc. Spento | Bruc. Funz. | Perdite al Mantello | | |
| | kW | kW | % | % | % | % | % | | |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| BENEFIT 20 | 24.1 | 26.7 | 90.30 | 86.1 | 0.6 | 7.9 | 1.8 | 108 | 5.8 |
| BENEFIT 20 K | 24.1 | 26.7 | 90.30 | 86.1 | 0.6 | 7.9 | 1.8 | 108 | 5.8 |
| BENEFIT 20 KI | 24.1 | 26.7 | 90.30 | 86.1 | 0.6 | 7.9 | 1.8 | 108 | 5.8 |
| BENEFIT 20 IS | 23.7 | 26.3 | 90.10 | 85.1 | 0.6 | 8.5 | 1.4 | 112 | 5.5 |
| BENEFIT 20 KS | 23.7 | 26.3 | 90.10 | 85.1 | 0.6 | 8.5 | 1.4 | 112 | 5.5 |
| BENEFIT 20 KIS | 23.7 | 26.3 | 90.10 | 85.1 | 0.6 | 8.5 | 1.4 | 112 | 5.5 |
| BENEFIT 20 KF | 23.8 | 26.2 | 90.80 | 85.1 | 0.6 | 7.2 | 2 | 116 | 6.95 |
| BENEFIT 24 K | 28.8 | 31.9 | 90.30 | 86.9 | 0.6 | 7.1 | 2.6 | 113 | 6.9 |
| BENEFIT 24 KI | 28.8 | 31.9 | 90.30 | 86.9 | 0.6 | 7.1 | 2.6 | 113 | 6.9 |
| BENEFIT 24 KS | 28 | 31 | 90.30 | 85.2 | 0.6 | 9 | 0.7 | 119 | 5.55 |
| BENEFIT 24 KIS | 28 | 31 | 90.30 | 85.2 | 0.6 | 9 | 0.7 | 119 | 5.55 |
| BENEFIT 24 KF | 27.3 | 30.0 | 91.00 | 85.2 | 0.6 | 7.1 | 1.9 | 116 | 7.1 |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| EXTERNA 20 K | 24.1 | 26.7 | 90.30 | 86.1 | 0.6 | 7.9 | 1.8 | 108 | 5.8 |
| EXTERNA 20 KS | 23.7 | 26.3 | 90.10 | 85.1 | 0.6 | 8.5 | 1.4 | 112 | 5.5 |
| EXTERNA 20 KIS | 23.7 | 26.3 | 90.10 | 85.1 | 0.6 | 8.5 | 1.4 | 112 | 5.5 |
| EXTERNA 24 K | 28.8 | 31.9 | 90.30 | 86.9 | 0.6 | 7.1 | 2.6 | 113 | 6.9 |
| EXTERNA 24 KS | 28 | 31 | 90.30 | 85.2 | 0.6 | 9 | 0.7 | 119 | 5.55 |
| EXTERNA 24 KIS | 28 | 31 | 90.30 | 85.2 | 0.6 | 9 | 0.7 | 119 | 5.55 |
| (1) con delta T = 50 °C | | | | | | | | | |

| Prodotto | Potenza Termica Max | | Rendimento utile | | A Pn (max) | | | | |
|------------------------------|---------------------|----------|------------------|-----------------------|-------------------|----------------|---------------------------|------------------------------------|----------|
| | Utile | Focolare | Pn | a carico rid.(30%) | Perdite al Camino | | Perdite al Mantello | Temper. fumi °C (delta T) | CO2 % |
| | | | | | Bruc. Spento | Bruc. Funz. | | | |
| | kW | kW | % | % | % | % | % | (1) | |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| RESIDENCE 20 K | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| RESIDENCE 20 KI | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| RESIDENCE 20 I | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| RESIDENCE 20 KIF | 23.8 | 26.2 | 90.80 | 85.1 | 0,6 | 7.2 | 2 | 116 | 6.95 |
| RESIDENCE 20 KS | 23.7 | 26.3 | 90.10 | 85.1 | 0,6 | 8.5 | 1.4 | 112 | 5.5 |
| RESIDENCE 20 KIS | 23.7 | 26.3 | 90.10 | 85.1 | 0,6 | 8.5 | 1.4 | 112 | 5.5 |
| RESIDENCE 20 IS | 23.7 | 26.3 | 90.10 | 85.1 | 0,6 | 8.5 | 1.4 | 112 | 5.5 |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| BENESSERE 24 KI | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| BENESSERE 24 KIS | 23.7 | 26.3 | 90.10 | 85.1 | 0,6 | 8.5 | 1.4 | 112 | 5.5 |
| BENESSERE 28 KI | 28.8 | 31.9 | 90.30 | 86.9 | 0,6 | 7.1 | 2.6 | 113 | 6.9 |
| BENESSERE 28 KIS | 28 | 31 | 90.30 | 85.2 | 0,6 | 9 | 0.7 | 119 | 5.55 |
| FUNZIONAMENTO CON GAS METANO | | | | | | | | | |
| PRONTACQUA 24 B | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| PRONTACQUA 24 BI | 24.1 | 26.7 | 90.30 | 86.1 | 0,6 | 7.9 | 1.8 | 108 | 5.8 |
| PRONTACQUA 24 BIS | 23.7 | 26.3 | 90.10 | 85.1 | 0,6 | 8.5 | 1.4 | 112 | 5.5 |
| PRONTACQUA 28 BI | 28.8 | 31.9 | 90.30 | 86.9 | 0,6 | 7.1 | 2.6 | 113 | 6.9 |
| PRONTACQUA 28 BIS | 28 | 31 | 90.30 | 85.2 | 0,6 | 9.1 | 0.6 | 119 | 5.55 |
| (1) con delta T = 50 °C | | | | | | | | | |